

TYPE 17 HEAVY DUTY LANDSCAPING SCREW

Self-drilling screw for heavy duty fastening of timber to timber where additional strength performance is required.

For landscaping or outdoor heavy timber construction projects.

Suitable for use with:

- Timber sleepers
- Heavy treated timbers
- Outdoor timber construction
- Fencing and gates



Technoguard Multi-layered Class 3 coating, for use in treated timbers

FIXCONN® TYPE 17 LANDSCAPE Screw	Pack Quantity	Bremick Product Code	Placemaker Product Code	Hex Driver	Screw Length (mm)	Grip Length (Min)	Shank Diameter (mm)	Threads per Inch
14-5 x 175 Class 3	50	SLSCT141754	4511962	6mm	175	95mm	5.8	5
14-5 x 200 Class 3	50	SLSCT142004	4511963	6mm	200	110mm	5.8	5
16-4 x 225 Class 3	50	SLSCT162254	4511964	6mm	225	130mm	7.1	4
16-4 x 250 Class 3	50	SLSCT162504	4511965	6mm	250	155mm	7.1	4

FIXCONN® TYPE 17 LANDSCAPE Screw	Mean Ultimate Pull Out (KN) in F5/JD4 Timber (H4 Treated Radiata Pine)							
	Embedment Depth							
	40mm	50mm	65mm	75mm	90mm	100mm	115mm	152mm
14-5 x 175 Class 3	7.86	7.86	7.86	7.86	6.43	6.43	6.43	5.8
14-5 x 200 Class 3	8.12	8.12	8.12	8.12	7.09	7.09	7.09	6
16-4 x 225 Class 3	9.53	9.53	9.53	9.53	9.53	8.22	8.22	8.22
16-4 x 250 Class 3	10.62	10.62	10.62	10.62	10.62	8.88	8.88	8.88



Hex Drive For excellent finish, robustness and ease of installation, as well as for positive drive under high installation torque.

Countersunk Ribbed Head For a secure flush finish.

Knurled Shank and Swarf Channel Helps prevent board lift and removes debris for faster drilling.

Technoguard Zinc Rich Alu-Flake Polymer Coating
Multi-layered Class 3 protective coating, compatible for use in treated timbers.

Type 17 Sharp Slotted Point Quickly self drills into hard and soft timbers.

