

# Grabcon® Frame



**GRABCON®**  
CONCRETE FRAMING SCREW

**FREE!**  
TX40  
Driver bit  
Included

**Fast, Efficient  
Bottom Plate Fixing!**

- For fixing timber to concrete or brick/ blockwork
- Domed washered head for high clamping force
- Non-expansion for close to concrete edge
- Can also be used for timber to timber applications
- Fully removable design (nothing left in the concrete)

Performance derived in accordance with  
AS 1720.1 - 2010 (timber Structures)



## Grabcon® Frame

**NEW**

☐ Grabcon® Concrete Framing Screw - Zinc Clear

ZINC INTERNAL

Part No.	Description	mm	drive	mm	qty	qty
GCF06102	6 x 102mm Concrete frame screw	6	T40	up to 45	100	1000

Grabcon Frame Specification details					Recommended Load 20 MPa Concrete (min.)		
Product	Description	Drill dia. (mm)	Head Dia. (mm)	Embedment Depth (mm)	Tension (kN)	Spacing (mm)	Edge Distance Min. (mm)
Frame Screw	6 x 102	6	21	57	1.45	200	45

**Note:** The Grabcon Frame screw anchor has been tested for pull-through capacity as referenced in AS 1720.1-2010. Maximum Recommend Load (pull-through / 35mm MGP10) = 3.4kN

ICCONS Pty Ltd.

Head Office, 12-18 Produce Drive,  
Dandenong South, Victoria, 3175

P: 03 9706 4344  
F: 03 9768 3329  
E: info@iccons.com.au

