

TYPE 17 SHARKS TOOTH™ CONSTRUCTION SCREW

Self-drilling screw for heavy duty fastening of timber to timber where additional strength and pull down performance is required.

For timber construction projects.

Suitable for use with:

- Timber frames
- Pergolas
- Outdoor timber construction
- Fencing and gates



For use in Category 5 Corrosive Environments

FIXCONN® TYPE 17 SHARKS TOOTH™ Screw	Pack Quantity	Product Code	Torx Driver	Screw Length (mm)	Grip Length (Min)	Shank Diameter (mm)	Threads per Inch
14-10 x 75 B8 Coating	100	STWSTC8140752T	T30	75	25mm	5.1	10
14-10 x 75 B8 Coating	250	STWSTC8140752K	T30	75	25mm	5.1	10
14-10 x 100 B8 Coating	100	STWSTC8141002T	T30	100	35mm	5.1	10
14-10 x 100 B8 Coating	250	STWSTC8141002K	T30	100	35mm	5.1	10

FIXCONN® TYPE 17 SHARKS TOOTH™ Screw	Single Shear (KN)	Axial Tensile (KN)	Torsional (Nm)	Mean Ultimate Pull Out (KN) in F5/JD4 Timber (H4 Treated Radiata Pine)			
				Embedment Depth			
				35mm	40mm	50mm	75mm
14-10 x 75 B8 Coating	11.1	20.3	20.8	8.9	10.1	12.1	N/A
14-10 x 100 B8 Coating	11.1	20.3	20.8	8.9	10.1	12.1	14.00



T30 Torx Drive Positive bit engagement allowing for maximum torque to be applied.

Washer head Broad holding powers means materials are brought together and held in position, resisting warp and head pull through.

Sharks Tooth™ Thread Provides an aggressive cutting action, dramatically decreasing installation time.

B8 coating Provides maximum corrosion protection in the harshest environments.

Type 17 Sharp Slotted Point Quickly self drills into hard and soft timbers.

