

Exterior Wood Screws

Strong-Drive® SDWS TIMBER Screw

Structural Wood-to-Wood Connections Including Ledgers

Designed to provide an easy-to-install, high-strength alternative to through-bolting and traditional lag screws. Strong-Drive® SDWS Timber screws are ideal for the contractor and do-it-yourselfer alike. It is code listed under IAPMO-UES ER-192 and meets 2012 and 2015 IRC® and IBC® code requirements for several common wood framing applications.

Features:


- Bold thread design provides superior holding power
- Patented 4CUT™ tip ensures fast starts, reduces installation torque and eliminates the need for pre-drilling in most applications
- Under-head nibs offer greater control when seating the head
- Large washer head provides maximum bearing area (0.75" head dia.)
- Size identification on all SDWS screw heads
- 6-lobe T-40 drive reduces driver-bit cam-outs, resulting in easier installations and longer bit life

Double-barrier coating provides corrosion resistance equivalent to hot-dip galvanization, making it suitable for certain exterior and preservative-treated wood applications, as described in the evaluation report.

Codes/Standards: IAPMO-UES ER-192, State of Florida FL13975, City of Los Angeles RR25906

For Technical Data and Loads, see pp. 292–305

U.S. Patents 5,897,280; 7,101,133



Double-Barrier Coating

Size Dia. x L (in.)	Thread Length (in.)	Retail Clam			Retail Pack			Mini-Bulk		Bulk	
		Fasteners Per Pack	Packs Per Master Carton	Model No.	Fasteners Per Pack	Packs Per Master Carton	Model No.	Fasteners Per Pack	Model No.	Fasteners Per Pack	Model No.
0.220 x 3	1½	12	10	SDWS22300DB-RC12	50	6	SDWS22300DB-R50	250	SDWS22300DBMB	950	SDWS22300DB
0.220 x 4	2¾	12	10	SDWS22400DB-RC12	50	6	SDWS22400DB-R50	250	SDWS22400DBMB	600	SDWS22400DB
0.220 x 5	2¾	12	10	SDWS22500DB-RC12	50	6	SDWS22500DB-R50	250	SDWS22500DBMB	600	SDWS22500DB
0.220 x 6	2¾	12	10	SDWS22600DB-RC12	50	6	SDWS22600DB-R50	250	SDWS22600DBMB	500	SDWS22600DB
0.220 x 8	2¾	12	10	SDWS22800DB-RC12	50	6	SDWS22800DB-R50	250	SDWS22800DBMB	400	SDWS22800DB
0.220 x 10	2¾	12	10	SDWS221000DBRC12	50	6	SDWS221000DB-R50	—	—	250	SDWS221000DB

Retail and mini-bulk packs include one 6-lobe, T-40 driver bit; bulk packs include two driver bits.